

Foldable Dimmable LED Grow Light

Product Description

Eagle Star Lighting ES-GL880A01-YY Foldable Dimmable LED Grow Light series works with ES-GL880A02-YY which are full spectrum grow light fixtures with Samsung +OSRAM LED Chips. The fixture has dimming function and spectrum tunable, including UV & IR light. They can provide more than 60% higher in PPFD compared with HID lamps with lower temperature, which increases the production and saves more than 50% power consumption. The fixtures can be used in many applications such as cannabis cultivation, vegetables, greenhouse, ornamental plants and so on.




- Model NO. ES-GL880A01-YY
- Fold & Sensen driver
- Samsung + Osram Chips
- Full Spectrum Red+UV+IR
- Input voltage 100-277VAC 50Hz/60Hz
- Ideal Working time: 10-14hours;
- Big&wide aluminum body with great heat dissipation
- The fixture can be connected one by one
- 0-10V dimming available
- Easy installation and maintenance
- Biggest Footprint: 4ft*4ft/5ft*5ft.
- Certificate: CE RoHS ETL cETL



Product Parameters

Input Power	720W	780W	820W	880W
LED Chips	Samsung +Osram + UV +IR			
Bars Qty	8 Bars	8 Bars	10 Bars	10 Bars
PPF	2016μmol/s	2184μmol/s	2296μmol/s	2464μmol/s
Efficacy	2.8-3.0 μmol/J			
Input Voltage	120-277VAC, 347-480VAC,50/60Hz			
Color Ratio	Full Spectrum Red+UV+IR			
Working Environment	-20°C~-40°C 45%~95%RH			
Certifications	CE, RoHS, ETL, cETL			
Product Size	L1180 * W1140 * H70mm(46.46" x 44.88" x 2.76")			
G.W	14.5KG(31.96lbs)			
Carton Size	L1275 * W180 * H675mm(50.2" x 7.1" x 26.6")			
Warranty	5 Years Warranty			

Product Size




Product Details




● Light ON Screen


Spectrum




PPFD($\mu\text{mol}/\text{m}^2/\text{s}$)




Height=6" / 152mm
780W F1 SPECTRUM 2.8 $\mu\text{mol}/\text{J}$



Height=12" / 305mm
780W F1 SPECTRUM 2.8 $\mu\text{mol}/\text{J}$




Height=24" / 609mm
780W F1 SPECTRUM 2.8μmol/J




780W Full Spectrum + Red 2.8 μmol/j

Connection



Installation



- Hang driver box
- Unfold the light, just one step to 180° horizontal position
- Hang the two extra cables on each side

<http://www.eaglestarlighting.com> TEL:+86 755 2369 6157 E-mail: info@eaglestarlighting.com
Address: 2#, first industrial zone, Songgang Town, Baoan District, Shenzhen,China

Applications

